

GI-388 TRUCK TYRE

Heavy Load Carrying Capacity On and Off the Highway

The GI-388 is specifically designed for heavy load applications such as waste haulers and sanitation vehicles utilizing front loaders that demand 10,000 lbs + load carrying capacity. Well-suited for both on and off-highway use, the GI-388 comes equipped with casing protection features, long mileage capability, and a cut and chip resistance compound. The advance tread compound resists the effects of tread chipping in high-scuff applications, lowering maintenance costs.




FEATURES AND BENEFITS

- Deeper tread all position tyres designed for on and off road service.
- > Stone ejectors in the centre groove.

On/Off Application



UNDER-TREAD RUBBER THICKNESS protects the belt package and casing.



STONE DEFENSE FEATURES effectively minimize rock and pebble packing to protect the belt package and casing from stone drilling.



CURB GUARD ON SIDEWALLS protects the casing from in-service damage.



ADVANCE TREAD COMPOUND resists effects of tread chipping during operation in high-scuff applications.





GI-388 TRUCK TYRE

| TYRES4U CODE | SIZE | PLY RATING | LOAD INDEX & SPEED SYMBOL | TL | OVERALL DIAM. (MM) | SECTION WIDTH (MM) | RIM WIDTH (CODE) | | TREAD |
|-----------------|-------------|---------------|------------------------------------|----|--------------------------|--------------------------|------------------|-------------|---------------|
| | | | | | | | MEASURING | APPROVED | DEPTH (MM) |
| 330293 | 7.50 R16 | 14 | 123/121K | TL | 809 | 215 | 6.0 | 5.50 - 7.00 | 13.2 |
| 330294 | 225/80R17.5 | | 123/122L | TL | 808 | 221 | 8.25 | 7.50 - 9.00 | 13.2 |
| 330192 | 265/70R19.5 | | 143/141J | TL | 878 | 256 | 7.50 | 7.50 - 8.25 | 14.7 |
| 314595 | 11R 22.5 | 16 | 148 / 145K | TL | 1063 | 286 | 8.25 | 7.50 - 8.25 | 20.6 |
| 330295 | 275/70R22.5 | | 148/145K | TL | 973 | 281 | 8.25 | 7.50 - 8.25 | 18.0 |
| 332893 | 295/80R22.5 | | 152/148K | TL | 1060 | 302 | 9.00 | 8.25 - 9.00 | 18.8 |
| 324485 | 315/80R22.5 | 20 | 156/150K | TL | 1083 | 312 | 9.00 | 9.00 - 9.75 | 19.1 |



