



RUN-FLAT TYRE TECHNOLOGY

Runflat Tyres have reinforced sidewalls that reduce deformation if the tyre sustains damage or a puncture; they can thus continue to be driven for at least a further 80 km at a maximum speed of 80 km/h.

Falken Runflat Tyres combine this 'limp-home' mode with top performance in all areas. Incidentally, manufacturers specify that Runflat Tyres must be used with a tyre pressure monitoring system because the tyres are so effective that drivers may not actually notice their tyre has a puncture.



NEO-T01 **NEO-T01 - Next Generation Tyre Manufacturing System, which offers ultra-high precision to create next generation tyres.**



< BEAD CARCASS WRAPPING
The bead carcass is wrapped in the shape of the finished tyre.



< BREAKER TREAD WRAPPING
The automated system wraps the breaker tread accurate to 1/100mm.



< RAW COVER
Since inflation is unnecessary, the shape is almost the same as the finished tyre.



< CURING
The rubber is vulcanised and cured to adhere to the metal core with high precision.

| RIM INCH | PRODUCT CODE | SIZE | TREAD PATTERN | NOTES | LOAD / SPEED |
|------------------|--------------|------------|---------------|----------|--------------|
| PASSENGER | | | | | |
| 18" | 330721 | 225/45RF18 | FK510 | Run-Flat | 95Y |
| | 330720 | 275/40RF18 | FK510 | Run-Flat | 103Y |
| | 330719 | 245/45RF18 | FK510 | Run-Flat | 100Y |
| | 330722 | 255/40RF18 | FK510 | Run-Flat | 99Y |
| | 330728 | 245/50RF18 | FK510 | Run-Flat | 104Y |
| 19" | 330725 | 225/40RF19 | FK510 | Run-Flat | 93Y |
| | 330723 | 245/40RF19 | FK510 | Run-Flat | 98Y |
| | 330726 | 255/35RF19 | FK510 | Run-Flat | 96Y |
| | 330724 | 275/35RF19 | FK510 | Run-Flat | 100Y |

tyres4u.co.nz
0800 888 973

